

(19)



Eur päisches Patentamt
European Patent Office
Office ur péen des br vets



(11)

EP 0 902 275 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

17.03.1999 Bulletin 1999/11

(51) Int Cl.⁶ G01N 21/88, B65B 57/02

(21) Application number: 98307390.9

(22) Date of filing: 11.09.1998

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(72) Inventors:

- Mullins, Michael J.
Chesterfield Virginia 23838 (US)
- Smith, Barry S.
Hopewell Virginia 23860 (US)

(30) Priority: 12.09.1997 US 928161

(71) Applicant: Philip Morris Products Inc.
Richmond Virginia 23234 (US)

(74) Representative:

Lloyd, Patrick Alexander Desmond
Reddie & Grose
16 Theobalds Road
London WC1X 8PL (GB)

(54) Fold inspection device for transparent overwrap film

(57) An imaging apparatus and process for inspecting polymeric film seals and folds. Incident light is applied to the package to cause either reflected or trans-

mitted light to reflect a pass through the poly wrap. The wrap affects the transmitted or reflected image in a manner which can be analyzed to determine the quality of the poly film application.




FIG. 4

EP 0 902 275 A1

D scription

[0001] This invention relates to inspection systems for over-wrap on packaged goods to ensure a complete and quality overwrap, proper graphics, and pack construction.

[0002] Inspection systems for packaged goods generally are known for use as quality control devices, and process control for manufacturing. Consumers may outright reject or return defectively packaged merchandise, for a variety of reasons. Improperly sealed consumer goods can raise safety and freshness concerns and perfectly good items will routinely be returned for refund and disposal with concomitant losses. Inspection is one way of ensuring a minimum of packaging defects.

[0003] High speed inspection systems have limited time to determine the acceptability of a product and are generally limited to examination of planar surface features, e.g. a misprint or a defect in the product exterior. Objects with a circular cross section, e.g. cigarettes, can be scanned sequentially using image scanning technology such as that in U.S. Patent Nos. 5,235,649, 5,366,096, 5,414,270, 5,013,905, and 4,976,544, which are incorporated herein in their entireties.

[0004] However, a transparent or partially transparent wrapper, e.g. a poly film wrapper, is invisible to normal optical inspection devices. A method for inspecting condition of the wrap is needed to ensure the packaging is intact and defective goods are not shipped.

[0005] Applicants have developed a novel imaging process to inspect polymeric film seals and folds. Incident light is applied to the package to cause either reflected or transmitted light to reflect a pass through the poly wrap. The wrap will affect the transmitted or reflected image in a manner which can be analyzed to determine the quality of the poly film application.

[0006] The invention will be further described by way of example with respect to the drawings, in which:

Fig. 1 is a perspective view of a package wrapped in poly film;

Fig. 2 is an end view of a package wrapped in poly film;

Fig. 3 is a perspective view of a package with a tear tape in the poly film;

Fig. 4 is a schematic view of an inspection system according to the present invention;

Fig. 5 is an end view of a defectively wrapped package;

Fig. 6 is a perspective view of an exemplary preferred system for detecting defects in planar surfaces;

Fig. 7 is the system of Fig. 6 with a defect present;

Fig. 8 is a perspective view of a pack and tear tape;

Fig. 9 is a perspective view of a pack and tear tape;

Fig. 10 is a perspective view of the illumination portion of an apparatus according to the present invention; and

Fig. 11 is a perspective view of the illumination portion of an apparatus according to the present invention.

[0007] The present inventive vision system is used to enhance product quality, but additionally is utilizable as a process inspection/control system. It allows an operator to see the manufacturing process dynamically as the cigarettes are being packaged. Therefore, a case of defectively packaged work is not packaged up and sent to inventory, to be discovered in a later quality audit, or worse, by a consumer. Thus, such a system is preferentially used in mainstream packaging.

[0008] Turning now to Fig. 1, an example of a packaged item is seen. The "ideal" wrap would have a total of 5 lines, i.e. lines 10, 12, 14, 16, and 18 as closure seams, with no overlap, or minimal overlap. Figure 2 illustrates the closure in an end view of the package of figure 1. The wrap system of Fig. 2 illustrates that the excess wrap may be easily folded over the cut to make a heat sealed or glued closure.

[0009] Lines 20, 22, 24, and 26 all originated with the same (upper or lower) edge of the poly film wrap. In a manner similar to wrapping any package, the excess film is physically folded over from side-to-side, then end-to-end, or vice versa. Sealing means, usually a heat treatment or the application of an adhesive substance, completes the wrapping procedure.

[0010] A properly wrapped package, depending on the sequence of folds, the placement of the overwrap, and amount of excess material, will have a distinctive "fold" pattern such as may be seen in Fig. 2.

[0011] An error in folding, placement of overwrap, or a tear in the wrap will drastically affect the pattern on the end. For example, in Fig. 5, the entire wrap is skewed to one side and the pattern is clearly visible as "wrong."

[0012] Poly film, usually, is invisible when used as an overwrap - allowing advertising indicia or package printing to show through. Thus, standard inspection techniques will fail to pick up the overwrap defects, be they misplacement, misfolding, tearing, wrinkling, or other defects.

[0013] Applicants novel system takes advantage of a unique property of clear or partially clear poly film. The film acts, for brief distances, as a light conductor. In many ways this is similar to fiber optic light transmission, when an endpoint is reached with a medium which has a different index of refraction, light appears to emanate from the endpoint, causing it to "glow."

[0014] Thus, as may be seen in Fig. 4, light source 40 sends incident light into the wrap itself. The light "escapes" from the poly film wrap at edges and folds where it reaches a reflective boundary. The escaped light 42 is captured via lens 44 to camera 46 and is thence sent to an image processor (not shown).

[0015] Image processing is undertaken to yield an image of the folds, or a clear surface image. In one embodiment, the surfaces without folds may be imaged for

defects. By way of example, Fig. 6 illustrates such a system. Incident light generator 60 generates incident light 62 which is projected into poly film 64. Strong reflected or diverted light will be picked up at lens 66 and focused on camera 68 for transmission to image analysis software.

[0016] Fig. 7 illustrates a defect being detected by the novel system. Light source 70 generates incident light 72 which enters the poly film surface 73. Defect 74 represents a missing portion of poly film wrap. The edges of the defect 75 are clearly illuminated by the light in the poly film. The defect is within field of vision 76 of camera 78 and lens 77. The image, including defect, is transmitted via cable or data transfer device 79 to be processed.

[0017] The image analysis of the present invention is performed by the following steps. The fold pattern or tear pattern is captured in the camera scan. Colour or black & white scanning may be used, but black and white scanning is faster, has a higher resolution, and is more easily adapted for partial scanning for example by a partial field scanning camera. The image is transferred via I/O circuitry or the like to the computer. The computer has reference images stored which are recognized as acceptable images. US Patent 5,537,670 provides a thorough explanation of such a system and is incorporated herein by reference.

[0018] A package such as that seen in Fig. 7, with its flaw in the surface, would be compared against a database of acceptable reference images, then rejected.

[0019] The system also may inspect for tear tape cuts and proper tear tape placement, as may be seen in Fig. 3.

[0020] While edges 32 and folds 30 may be inspected, so too may be tear tape protrusion 34 and tear tape cuts 36, for placement and cutting completeness.

[0021] The inspection system may also take advantage of the blocking characteristics of a poly wrap film which has printing upon it. The image printed upon the film will act to block light transmission in a particular pattern, or reduce it. The system can rapidly "learn" this light scattering by allowing it to store acceptable images in its database. Then, occluded light patterns are learned as acceptable. Other wrap patterns likewise may be learned in a manner similar to the system's initial programming with conventional packaging fold and surface images e.g. as seen in figures 8-11.

[0022] Camera devices may be standard video cameras, charge-coupled-devices, or other optical detectors which may receive transmitted or reflected light from the poly film.

[0023] The light source utilized may be fluorescent, incandescent, solid state generated (e.g. LED constant or "pulsed"), infrared, or other type of light, so long as the wavelength will be transmitted by the poly film. An exemplary strobe is manufactured by EG&G, Inc. of Salem, Massachusetts. Part number 2020 is particularly useful.

[0024] An apparatus according to the present inven-

tion will be useful for the optical inspection of objects wrapped in a transparent or semi-transparent material.

[0025] The transparent material is a filmic material, laminated or unlaminated, coated or uncoated, with or without an image on the film. The film is made from polypropylene, polyethylene, cellophane, or the like. Thickness may be in the range of from about 2.5 μm (0.1 mil) to 250 μm (10 mils), preferably from the range of 12 μm (0.5 mil) to 75 μm (3 mil); more preferably from about 25-50 μm (1-2 mils), most preferably about 37 μm (1.5 mils).

[0026] The apparatus will have a light source positioned such that light enters the transparent wrap material at an intensity greater than ambient light conditions, and an optical detector which receives light from the transparent wrap material. A light source from 1 to 100 watts may be used, but it has been found most efficient to occlude the ambient light to some extent and use lights in the lower end of that range, from 1-25 watts, and preferably from 1-15 watts output.

[0027] The apparatus will further be equipped with an image analyser which receives input from the optical detector and determines the acceptability of that input. Panasonic's GPMF702D black & white camera is particularly useful and is commercially available for use as the optical detector. Such a camera is capable of partial scanning which results in increased frame speed and higher inspection rates, and is easily networked into a 486 computer by a conventional means.

[0028] The presently preferred controller is a 486 Pentium™ based processing unit, manufactured and designed by PPT of Eden Prairie, Minnesota under the designation VPC 400 Vision Processing Controller. The controller preferably is linked to an optical image display, which can display the images generated visually to an operator who can adjust or halt a packaging machine manually. An automated feedback loop may also be provided for correcting certain known defects; e.g. from a library of "defective" images, certain pre-programmed corrective steps may be automatically executed by the controller and inputted into the packaging machine.

[0029] One of skill in the art, having regard for this disclosure, may make many modifications and improvements hereto without departing from the scope of the appended claims.

Claims

1. Apparatus for the optical inspection of objects wrapped in a transparent or semi-transparent material (64) comprising:

a light source (40) (60) (70) positioned such that light enters the transparent or semi-transparent material (64) at an intensity greater than ambient light conditions;
an optical detector (46) (68) (78) which receives

light from the transparent wrap material; and an image analyzer which receives input from the optical detector and determines the acceptability of that input.

2. Apparatus according to claim 1 wherein the light source (40) (60) (70) is positioned perpendicular or oblique to the object to be inspected.
3. Apparatus according to claim 1 or 2 wherein the light source (40) (60) (70) is incandescent or fluorescent.
4. Apparatus according to claim 1, 2 or 3 wherein the light source (40) (60) (70) is solid state.
5. An apparatus as claimed in claim 4 wherein the light source (40) (60) (70) comprises at least one light emitting diode.
6. Apparatus according to any of claims 1 to 5 wherein the light from the light source (40) (60) (70) is ultra-violet.
7. Apparatus according to any of claims 1 to 5 wherein the light from the light source (40) (60) (70) is infra-red.
8. Apparatus according to any of claims 1 to 5 wherein the light from the light source (40) (60) (70) is visible light.
9. Apparatus according to any preceding claim wherein the light source (40) (60) (70) emits from 1 to 100 watts.
10. Apparatus as claimed in claim 9 wherein the light source (40) (60) (70) is from 1-25 watts in power.
11. Apparatus according to any preceding claim wherein the optical detector (46) (66) (76) is a camera.
12. Apparatus according to claim 11 wherein the camera (46) (66) (76) is a charge-coupled device.
13. Apparatus according to claim 11 or 12 wherein the camera (46) (66) (76) is sensitive to infrared or ultraviolet.
14. Apparatus according to any of claims 11 to 13 wherein the camera (46) (66) (76) is a scanning black and white camera.
15. Apparatus according to any of claims 11 to 14 wherein the camera (46) (66) (76) is a partial field scanning camera.
16. Apparatus according to any preceding claim where-

in the light source (40) (60) (70) is constant.

17. Apparatus according to any of claims 1 to 15 wherein the light source (40) (50) (70) is pulsed or strobed.
18. Apparatus according to any preceding claim further comprising an optical display.
19. Apparatus according to any preceding claim for the optical inspection of cigarette packages wrapped in a transparent or semi-transparent polymeric filmic wrap material (64).
20. A method for optically inspecting package wrapped in a transparent or semi-transparent wrapper (64) comprising:
 - providing a wrapped article to be inspected; directing incident light upon the article such that at least some of the incident light enters the wrapper (64) and the wrapper acts as a wave-guide to the light;
 - detecting the light escaping from the wrapper;
 - examining the pattern of escaped light and comparing it to known patterns; and
 - determining the acceptability of the wrapped article by comparing the pattern of escaped light to a database of known images of patterns of escaped light from acceptable packages.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

FIG. 8





FIG. 9







FIG. 10





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 30 7390

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 6)
X	EP 0 523 441 A (EASTMAN KODAK CO) 20 January 1993 * abstract *	1, 3, 6, 8-11, 13, 17, 19	G01N21/88 B65B57/02
Y	* column 1, line 38 - line 49 * * column 2, line 22 - line 28 * * column 4, line 8 - line 11 * * column 4, line 50 - column 5, line 5 *	2, 4, 5, 7, 12, 16, 20	
Y	US 4 053 056 A (DAY JOHN HERBERT) 11 October 1977 * column 4, line 21 - line 62 * * column 5, line 6 - line 10 * * column 5, line 48 - line 56 *	2, 4, 5	
Y	US 4 972 494 A (WHITE KENNETH W ET AL) 20 November 1990 * abstract * * column 11, line 21 - line 29 *	12, 16	
Y	US 5 627 638 A (VOKHMIN PETER A) 6 May 1997 * abstract * * column 2, line 66 - column 3, line 16 * * figure 2 *	20	TECHNICAL FIELDS SEARCHED (Int. Cl. 6) B65B G07C G01N B07C G06T A24C G06K
Y	EP 0 373 796 A (AMERICAN TELEPHONE & TELEGRAPH) 20 June 1990 * abstract * * figure 1 *	7	
A	US 5 264 700 A (TOMMASINI BRUNO ET AL) 23 November 1993 * abstract * * column 1, line 24 - line 52 * * column 2, line 10 - line 20 * * column 2, line 23 - line 26 *	1, 2, 6, 11, 13, 17	
-/-			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 21 January 1999	Examiner Verdoordt, E
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.82) (P4/C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 30 7390

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	US 3 939 984 A (BUTNER DEAN C ET AL) 24 February 1976 * column 7, line 36 - line 42 * * column 7, line 61 - column 8, line 2 * * column 8, line 12 - line 38 * * figure 9 *	1, 2, 8, 17	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 21 January 1999	Examiner Verdoodt, E
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P4/C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 98 30 7390

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-01-1999

Patent document cited in search report.	Publication date	Patent family member(s)	Publication date
EP 0523441 A	20-01-1993	US 5101609 A	07-04-1992
		JP 5270510 A	19-10-1993
US 4053056 A	11-10-1977	BR 7704730 A	28-03-1978
		CA 1090897 A	02-12-1980
		DE 2731477 A	26-01-1978
		GB 1545728 A	16-05-1979
		JP 1108113 C	13-08-1982
		JP 53033647 A	29-03-1978
		JP 56052769 B	15-12-1981
US 4972494 A	20-11-1990	EP 0330495 A	30-08-1989
		JP 1269034 A	26-10-1989
US 5627638 A	06-05-1997	IL 106207 A	04-08-1996
		AU 687084 B	19-02-1998
		AU 7254394 A	24-01-1995
		DE 69409805 D	28-05-1998
		DE 69409805 T	13-08-1998
		EP 0706645 A	17-04-1996
		WO 9501558 A	12-01-1995
EP 0373796 A	20-06-1990	US 4988875 A	29-01-1991
		AU 613253 B	25-07-1991
		AU 4585989 A	05-07-1990
		CA 2001666 A,C	13-06-1990
		JP 1971049 C	27-09-1995
		JP 2223849 A	06-09-1990
		JP 6092942 B	16-11-1994
		KR 9603194 B	06-03-1996
US 5264700 A	23-11-1993	IT 1246931 B	29-11-1994
		DE 4212676 A	22-10-1992
		GB 2254919 A,B	21-10-1992
		JP 5132048 A	28-05-1993
US 3939984 A	24-02-1976	AR 210475 A	15-08-1977
		AT 353184 B	25-10-1979
		AT 883675 A	15-03-1979
		AU 8681175 A	26-05-1977
		BE 835785 A	16-03-1976
		BR 7507698 A	24-08-1976
		CA 1021722 A	29-11-1977
		CH 607703 A	13-10-1978
		CS 199608 B	31-07-1980
		DE 2552131 A	01-07-1976

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO. 88 000 000

EP 98 30 7390

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on 21-01-1999. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-01-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3939984 A		DK 523175 A	21-06-1976
		FR 2294915 A	16-07-1976
		GB 1536874 A	20-12-1978
		IE 43760 B	20-05-1981
		JP 1088892 C	23-03-1982
		JP 51135791 A	24-11-1976
		JP 56034485 B	11-08-1981
		JP 51080487 A	14-07-1976
		LI 73836 A	11-06-1976
		SE 7513566 A	22-06-1976
		SE 431188 B	23-01-1984
		SE 7513052 A	21-06-1976
		ZA 7507293 A	24-11-1976

EPO FORM P/US

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

